

# Kamco™ Division

## EZ-ROLL PLUS™ BLACK COATED INSULATED COPPER TUBE

*EZ-Roll Plus™ Black* is a seamless, factory-assembled insulated copper tube for use in air conditioning, refrigeration and HVAC applications.

Featuring a black polymeric protective coating, *EZ-Roll Plus™ Black* provides exceptional tear-resistance when being installed through or around rough contours, eliminating insulation repairs while providing additional layout options.

Available in standard line set configurations, ductless mini split and single line options, products are available to service all HVAC and refrigeration applications.

### **Insulation Specifications:**

- 25/50 rated to ASTM E 84
- - 297°F to 220°F Expanded Operating Temperature Range
- Enhanced UV Resistance



## EZ-Roll PLUS™ Black for air conditioning and refrigeration applications

**EZ-Roll Plus™ Black** insulated copper tubing is the latest introduction from Great Lakes Copper LTD for line set, refrigeration and general HVAC applications. Proudly introducing **EZ-Roll Plus™ Black**, Great Lakes Copper LTD continues to bring forward new and innovative solutions to the challenges of tomorrow.

Proving to be its most distinct characteristic, the durability of the black coating is its most significant advantage, providing exceptional tear-resistance wherever it is installed. Traditional elastomeric insulation often becomes torn or removed entirely when it comes into contact with sharp or rough contours, often requiring on-site repair and contributing to a loss of efficiency in the system. **EZ-Roll Plus™ Black** has an exterior coating that can handle installations through rough concrete access points, through wooden joists or other rough surface conditions. Eliminating tears avoids repairs and saves you time.

The black coating also features UV and moisture-resistant qualities, securing against thermal losses and providing longevity when in direct contact with sunlight and UV rays.

**EZ-Roll Plus™ Black** is available in standard line set configurations for residential or commercial air conditioning, dual-line insulated ductless mini split options for split heating or cooling systems and available as single line insulated options for dedicated thermal or cooling applications.

CONFIGURATION	COPPER SIZE RANGE	INSULATION THICKNESS	LENGTHS (FEET)
COPPER SIZE	1/4" - 7/8"	1/2", 3/4"	15' - 164'



**TEAR-RESISTANT COATING**



**COATING TEXTURE PROVIDES EXCEPTIONAL DUCTILITY**



**UV AND MOISTURE RESISTANT**



**PACKAGING FEATURES TEAR-AWAY FRONT PANEL**